


These 2-turn rings are ideal for applications with high thrust loads and are designed to fit into a groove established by DIN specifications.



Free Diameter & Ring Measurements


Housing Diameter & Groove Dimensions

RING	HOUSING		GR	OOVE SIZ	E					THRUST L	.OAD (N)			
NO.	DIAMETER	DIAMETER		WIDTH		DEPTH	FRE		THICK	NESS	SECTION		RING	GROOVE
	(DIAMETER						Safety	Safety
	(mm) Dh	Dg	Tol.	W	Tol.	d	Df	Tol.	т	Tol.	S	Tol.	factor of 3	factor of 2
DKR-13	13	13.6	101.	1,10	101.	0.3	13,72	101.	0.99	101.	1.40	101.	13474	1901
DKR-14	14	14,6	+0.11	1,10	1	0,3	14,75		0,99		1,40		14510	2047
DKR-15	15	15,7	-0,00	1,10	1	0,3	15,85		0,99		1,40		15547	2559
DKR-16	16	16,8	0,00	1,10		0.4	16,97		0,99		1,46		16583	3119
DKR-17	17	17.8	1	1.10	1	0.4	17,98	+0.33	0.99		1,65		17620	3314
DKR-18	18	19,0		1,10	1	0,5	19,18	-0,00	0,99		1,91		18656	4386
DKR-19	19	20,0	+0,13	1,10	1	0,5	20,19		0,99	±0,05	1,91		19693	4630
DKR-20	20	21,0	-0.00	1,10		0,5	21,21		0,99		1,91		20729	4874
DKR-21	21	22,0	1	1,10		0,5	22,23		0,99		1,91		21766	5117
DKR-22	22	23,0		1,10		0,5	23,23		0,99		1,91		22802	5361
DKR-23	23	24,1		1,30	1	0,6	24,33		1,14		2,18		23853	6165
DKR-24	24	25,2		1,30	+0,14	0,6	25,45		1,14		2,18	±0,10	24891	7018
DKR-25	25	26,2	+0,21	1,30	-0,00	0,6	26,45		1,14		2,18		25928	7310
DKR-26	26	27,2	-0,00	1,30		0,6	27,48		1,14		2,18		26965	7603
DKR-27	27	28,4		1,30		0,7	28,68		1,14		2,41		28002	9211
DKR-28	28	29,4		1,30		0,7	29,69		1,14		2,41		29039	9552
DKR-29	29	30,4		1,30		0,7	30,71		1,14		2,41		30076	9893
DKR-30	30	31,4		1,30		0,7	31,71	+0,38	1,14		2,41		31113	10235
DKR-31	31	32,7		1,30		0,9	33,02	-0,00	1,14		2,41		32150	12842
DKR-32	32	33,7		1,30		0,9	34,04		1,14		2,41		33187	13256
DKR-33	33	34,7	+0,25	1,30		0,9	35,05		1,14		2,41		34224	13670
DKR-34	34	35,7	-0,00	1,60	-	0,9	36,07		1,44		3,25		44541	14085
DKR-35	35	37,0		1,60		1,0	37,38		1,44		3,25		45851	17058
DKR-36	36	38,0		1,60		1,0	38,39		1,44		3,25		47161	17545
DKR-37	37	39,0		1,60		1,0	39,40		1,44		3,25		48471	18032
DKR-38	38	40,0		1,60		1,0	40,41		1,44		3,25		49781	18520

www.rotorclip.com

+1 732.469.7333 • sales@rotorclip.com





Free Diameter & Ring Measurements


Housing Diameter & Groove Dimensions

RING	HOUSING		0	GROOVE SIZ	ZE .				THRUST LOAD (N)					
NO.	DIAMETER (mm)	DIAMETER		WIDTH		DEPTH	FRE DIAME	TER	THICKNESS		SECTION		RING Safety factor of	GROOVE Safety factor of
	Dh	Dg	Tol.	W	Tol.	d	Df	Tol.	T	Tol.	S	Tol.	3	2
DKR-40	40	42,5		1,85		1,3	42,93		1,69		4,01		61498	24368
DKR-41	41	43,5	+0,25	1,85		1,3	43,94		1,69		4,01		63036	24977
DKR-42	42	44,5	-0,00	1,85		1,3	44,96	+0,51	1,69	± 0.05	4,01	±0,10	64573	25586
DKR-45	45	47,5]	1,85		1,3	47,98	-0,00	1,69		4,01		69186	27414
DKR-47	47	49,5		1,85			49,99		1,69		4,01		72261	28633
DKR-48	48	50,5		1,85			51,00		1,69		4,01		73798	29242
DKR-50	50	53,0]	2,15		1,5	53,54		1,93		5,08		87790	36552
DKR-51	51	54,0]	2,15		1,5	54,54]	1,93		5,08		89546	37283
DKR-52	52	55,0	-	2,15	1	1,5	55,55	+0,63	1,93		5,08		91302	38014
DKR-55	55	58,0		2,15		1,5	58,57		1,93	±0,08	5,08	±0,12	96569	40207
DKR-56	56	59,0]	2,15	+0,14	1,5	59,59		1,93		5,08		98325	40938
DKR-57	57	60,0]	2,15	-0,00	1,5	60,60		1,93		5,08		100081	41669
DKR-58	58	61,0]	2,15		1,5	61,62]	1,93		5,08		101836	42400
DKR-60	60	63,0	+0,30	2,15		1,5	63,63		1,93		5,08		105348	43863
DKR-62	62	65,0	-0,00	2,15	1	1,5	65,66		1,93		5,08		108860	45325
DKR-63	63	66,0	1	2,15		1,5	66,67		1,93		5,08		110615	46056
DKR-64	64	67,0	1	2,15		1,5	67,67		1,93		5,08		112371	46787
DKR-65	65	68,0	1	2,65		1,5	68,67		2,41		5,08		135725	47518
DKR-67	67	70,0	1	2,65		1,5	70,67	1	2,41		5,08		139901	48980
DKR-68	68	71,0	1	2,65		1,5	71,67	1	2,41	1	5,08		141989	49711
DKR-70	70	73,0]	2,65		1,5	73,67]	2,41		5,08		146165	51173
DKR-72	72	75,0]	2,65		1,5	75,67	+0,76	2,41		5,08		150341	52635
DKR-75	75	78,0]	2,65		1,5	78,68	-0,00	2,41		5,08		156605	54828
DKR-76	76	79,0]	2,65		1,5	79,68		2,41		5,08		158694	55559
DKR-78	78	81,0	+0,35	2,65		1,5	81,69]	2,41		5,08		162870	57021
DKR-80	80	83,5	-0,00	2,65		1,8	84,19]	2,41	1	6,05	±0,13	167046	68231





These 2-turn rings are ideal for applications with high thrust loads and are designed to fit into a groove established by DIN specifications.



Free Diameter & Ring Measurements


Housing Diameter & Groove Dimensions

RING	HOUSING			GROOVE	SIZE			THRUST L	.OAD (N)					
NO.	DIAMETER	DIAMETER		V	VIDTH	DEPTH	EPTH FREE		THICK	NESS	SECTION		RING	GROOVE
							DIA	DIAMETER					Safety	Safety
	(mm)												factor of	factor of
	Dh	Dg	Tol.	W	Tol.	d	Df	Tol.	T	Tol.	S	Tol.	3	2
DKR-82	82	85,5		2,65	+0,14 -0,00	1,8	86,20	+0,76 -0,00	2,41		6,05		171222	69936
DKR-85	85	88,5]	3,15		1,8	89,20		2,91		6,05		214309	72495
DKR-88	88	91,5	+0,35	3,15		1,8	92,21]	2,91		6,05		221873	75054
DKR-90	90	93,5	-0,00	3,15		1,8	94,21	+0,89	2,91	± 0.08	6,05		226915	76759
DKR-92	92	95,5]	3,15		1,8	96,22	-0,00	2,91		6,05		231958	78465
DKR-95	95	98,5]	3,15		1,8	99,24		2,91		6,05		239522	81024
DKR-98	98	101,5]	3,15		1,8	102,26		2,91		6,05		247068	83583
DKR-100	100	103,5		3,15		1,8	104,29		2,91		6,05		252128	85288
DKR-102	102	106,0		4,15		2,0	106,79		3,89		6,73		343778	99422
DKR-105	105	109,0		4,15		2,0	109,79		3,89		6,73	$\pm 0,13$	353889	102346
DKR-108	108	112,0	+0,54	4,15		2,0	112,80		3,89		6,73		364000	105270
DKR-110	110	114,0	-0,00	4,15		2,0	114,83		3,89		6,73		370741	107220
DKR-112	112	116,0		4,15	+0,18	2,0	116,84		3,89		6,73		377482	109169
DKR-115	115	119,0		4,15	-0,00	2,0	119,86	+1,30	3,89		6,73		387593	112093
DKR-120	120	124,0		4,15		2,0	124,92	-0,00	3,89		6,73		404445	116967
DKR-125	125	129,0]	4,15		2,0	129,97		3,89		6,73		421297	121840
DKR-127	127	131,0]	4,15		2,0	131,97		3,89	±0,10	6,73		428038	123790
DKR-130	130	134,0]	4,15		2,0	135,00		3,89		6,73		438149	126714
DKR-135	135	139,0	+0,63	4,15		2,0	140,03		3,89		6,73		455001	131588
DKR-140	140	144,0	-0,00	4,15		2,0	145,11		3,89		6,73		471852	136461
DKR-145	145	149,0]	4,15		2,0	150,11		3,89		6,73		488704	141335
DKR-150	150	155,0]	4,15		2,5	156,13		3,89		7,92		505556	182761
DKR-155	155	160,0]	4,15		2,5	161,19	+1.40	3,89		7,92		522408	188853
DKR-160	160	165,0]	4,15		2,5	166,22	-0.00	3,89		7,92	±0,15	539260	194945
DKR-165	165	170,0]	4,15		2,5	171,27]	3,89		7,92		556112	201037
DKR-170	170	175,0]	4,15	l	2,5	176,33]	3,89		7,92		572964	207129

www.rotorclip.com

+1 732.469.7333 • sales@rotorclip.com





Free Diameter & Ring Measurements

Housing Diameter & Groove Dimensions

RING	HOUSING		GRO	OVE SIZE					THRUST LOAD (N)					
NO.	DIAMETER	DIAI	METER	TER WIDTH DEPTH			FRE	THICKN	IESS	SECTION		RING	GROOVE	
							DIAME	TER					Safety	Safety
	(mm)												factor of	factor of
	Dh	Dg	Tol.	W	Tol.	d	Df	Tol.	T	Tol.	S	Tol.	3	2
DKR-175	175	180,0	+0,63 -0,00	4.15		2,5	181,36	+1,40	3,89		7,92		589815	213221
DKR-180	180	185,0		4.15		2,5	186,39	-0,00	3,89]	7,92		606667	219313
DKR-185	185	190,0		4.15		2,5	191,44		3,89	±0,10	7,92		623519	225405
DKR-190	190	195,0		4.15		2,5	196,47]	3,89]	7,92		640371	231497
DKR-195	195	200,0	+0.72	4.15		2,5	201,52		3,89]	7,92		657223	237589
DKR-200	200	205,0	-0.00	4.15		2,5	206,58]	3,89		7,92		674075	243681
DKR-210	210	216,0		5.15	+0,18	3,0	217,58	+1,78	4,86		9,53		884268	307038
DKR-220	220	226,0		5.15	-0,00	3,0	227,66	-0,00	4,86]	9,53	±0,15	926376	321659
DKR-230	230	236,0		5.15		3,0	237,72	1	4,86	1	9,53		968484	336280
DKR-240	240	246,0		5.15		3,0	247,80		4,86]	9,53		1010592	350900
DKR-250	250	256,0		5.15		3,0	257,89]	4,86]	9,53		1052700	365521
DKR-260	260	268,0		5.15		4,0	269,93	1	4,86	1	11,18		1094808	506856
DKR-270	270	278,0	+0.81	5.15		4,0	280,01		4,86]	11,18		1136916	526351
DKR-280	280	288,0	-0.00	5.15		4,0	290,09		4,86	1	11,18		1179024	545845
DKR-290	290	298,0		5.15		4,0	300,15	1	4,86	±0,13	11,18		1221132	565340
DKR-300	300	308,0		5.15		4,0	310,24	+3,05	4,86	1	11,18		1263241	584834
DKR-310	310	320,0		6.20		5,0	322,25	-0,00	5,87	1	12,70		1576625	755411
DKR-320	320	330,0		6.20		5,0	332,33	1	5,87]	12,70		1627484	779779
DKR-330	330	340,0		6.20		5,0	342,42	1	5,87	1	12,70		1678342	804147
DKR-340	340	350,0		6.20		5,0	352,50		5,87	1	12,70		1729201	828515
DKR-350	350	360,0	+0.89	6.20	+0,22	5,0	362,56		5,87]	12,70	±0,19	1780060	852883
DKR-360	360	370,0	-0.00	6.20	-0,00	5,0	372,64	+3,56	5,87]	12,70		1830919	877251
DKR-370	370	380,0		6.20		5,0	382,73	-0,00	5,87]	12,70		1881778	901619
DKR-380	380	390,0		6.20		5,0	392,79		5,87]	12,70		1932637	925987
DKR-390	390	400,0		6.20		5,0	402,84		5,87]	12,70		1983496	950355
DKR-400	400	410,0		6.20		5,0	412,93		5,87]	12,70		2034354	974723